



PRODUCT INTRODUCTION

——Smart lighting happy life





Contents

I .	Company profile	01
II .	Zigbee 3.0 、 RF、 WiFi features	02
III .	Product classification	04
IV .	Zigbee pro series	07
V .	WiFi series	32
VI .	Other products	35
VII .	Function Introduction	39



About Gledopto

GLEDOPITO CO.LTD focuses on developing new products with innovative idea and the latest technology.

WIRELESS TECHNOLOGY:

Manufacturing traditional LED products reborn with 2.4GHz standard ZIGBEE technology, RF remote control technology and rich LED experience.

GLEDOPITO CO., LTD is an industrial trading company located in Shenzhen, CN. since 2010.

üWith R&D team to provide OEM solution and customized products

üVarious products be released almost each season with the latest design

üOwns the updated machine, professional team with proficient skill

PRINCIPLE:

Good faith cooperation to create a win-win situation

Good quality is our responsibility to customers

Good quality is the key sustainable condition

Certificates





ZIGBEE3.0

Gledopto system communicates with most zigbee systems from other providers, so you can easily extend the system with more different items.

- all your lamps can be operated from one bridge
- deliver a high interoperable wireless mesh network
- extremely low-power consumption
- remote control for convenience and security

HOW IT WORKS

1. plug GLEDOPTO light source to a power supply
2. connect the Zigbee Bridge(optional) to a power supply and connect to your router
3. download and install the Zigbee Bridge App
4. search and connect the light on the App's settings
5. create and modify your own zigbee network

Advantages

- Voice commands and smartphone activate
- Receive and process commands from multiple devices at the same time
- Operate and remember default/custom scenarios

RF

It is perfect for every smart home beginner who want to test the wireless control.

- No require the Zigbee bridge
- pairing and operate process even more simple

HOW IT WORKS

MATCH (more about "DELETE process" please refer the User Instruction)

1. battery power the wall switch or manual remote control
2. within 3s of power on the gledopto light source, press zone "1" (of any group you want the light in) to do the pairing.
3. the indicator turns green to show successfully paring
4. create and modify your own RF lights system

Advantages

- Each remote can match one or more receiver for group control
- Nine kinds of default color dynamic scenarios
- Ultra sensitive color&CCT adjustment touch wheel/bar

WIFI

is a trademark of the Wi-Fi Alliance manufacturers as a brand certification for their products and is a wireless LAN technology created in the IEEE 802.11 standard.

FEATURES

1. Health and safety
2. No wiring required
3. Its radio wave coverage range is wide
4. Speed is not only fast, but also highly reliable



GLEDOPITO



ZIGBEE 3.0




• **Power-up speed**
Within 1S




• **Lighting color transition to CCT temperature**
Smoother



• **Zigbee distance**
Mesh network




• **Minimum brightness**
Darker




• **Adjust brightness**
Smoother



• **Adjust color**
Smoother



• **Multiple lights powered up simultaneously**
Lights up almost simultaneously



• **Search after resetting**
It's easy to search for lights



ZigBee 3.0 RGB CCT Controller Pro (With reset button)



ZigBee 3.0 RGB CCT Mini Ultra Thin LED Controller



5 in 1 Intelligent Controller



MINI 5 in 1 Controller



2 Wires CCT/DIM 2 in 1 LED Controller Pro



Zigbee Triac AC Dimmer



Zigbee + RF Digital RGB Strip Controller



RGB CCT LED Controller (MIX)



DC12V 3-Button Controller Set (with power supply)



MINI Controller Pro



LED Downlight Pro



LED Downlight Pro IP54



6W LED Downlight Pro CRI>90



6W LED Downlight Pro UGR<20



9W E26 LED Downlight Pro



A60 7W LED Filament Bulb Pro



ST64 7W LED Filament Bulb Pro



G95 7W LED Filament Bulb Pro



4W Candle Bulb Pro



6W LED Bulb Pro



12W LED Bulb Pro



4W LED MR16 Pro



5W LED GU10 Pro



WiFi 5-in-1 LED Controller



WiFi LED Controller



10W Flood Light Pro



30W Flood Light Pro



60W Flood Light Pro



100W Flood Light Pro



200W Flood Light Pro



400W Flood Light Pro



12W Garden Lamp Pro



7W Garden Light Pro
AC 100~240V




7W Garden Light Pro
AC/DC 24V



7W Garden light pro
AC 100~240V



7W Garden light pro
AC/DC 24V





ZIGBEE PRO SERIES

My room is up to me.

ZIGBEE 3.0 LED CONTROLLER PRO

Reset function:

- *1.Short press once to turn on or off
- *2.Long press >2 seconds, the LED strip blinks 3 times, Reset is done successful.



Function Introduction>>>



1.Small and light weight
No space, simple installation.

2.Dual white and Color
color, brightness, color temperature can be adjusted.

3.Press type Design
Wiring is more convenient.

4.Fireproof material
High temperature resistance.



RGB CCT Controller Pro (With reset button)




RGBW controller pro (With reset button)



WW/CW controller pro (With reset button)



Dimmer controller pro (With reset button)



Qty: 100pcs/carton
carton size: 300x270x200mm


Power connector>>>



- ① 5.5x2.1mm DC Socket
- ② ③ V+,V- power interface



Model NO.	GL-C-008P	Input voltage	DC12~24~36~48~54V
Output current	5A Max	Total output current	10A Max
Size	89x23.5x48mm	IP Rate	IP20
N.W.:	54.8g	G.W.:	67.2g
Operating temperature	-20°C~60°C		



Zigbee 3.0 Mini Ultra Thin LED Controller



Voice control



APP control



2.4G RF Remote control



Frequency settings



Power on status settings



Qty: 200pcs/carton
carton size: 328x190x260mm



Light weight >>>



Mini RGB CCT Ultra Thin LED controller



Mini RGBW Ultra Thin LED controller




Mini WW/CW Ultra Thin LED controller



Mini Dimmer Ultra Thin LED controller

Product Name	Zigbee Mini RGB CCT Ultra Thin LED Controller Pro		
Size	70x10x36MM	Product model	GL-C-008P(Mini)
Total output current	6A Max	Input voltage	DC 5-24V
Output current/Channel	3A Max	IP Rate	IP20
Working temperature	-20°C~45°C	Material	Fireproof material
N.W	23.5G	G.W	42.4G



Controller Parameter >>>

Product name	Zigbee 3.0 Mini controller pro
Input voltage	DC5V
Size	11x22x43mm
Total output current	2A Max
IP Rate	IP20
Operating temperature	-20°C~60°C
	Common anode
	Constant voltage

Light strip parameter >>>

Input voltage	DC5V
Size of section	33.3mm(3LEDs)
Voltage power/m	10W/m(MAX)
Strip length	2m
PCB width	12mm
CCT	2700~6500K

ZIGBEE 3.0

ZIGBEE 5-IN-1 SMART LED CONTROLLER

Voice control

APP control

2.4G RF Remote control

Frequency settings



Power on status settings

Five modes

Product Name	5in1 intelligent controller
Total output current	10A Max
Output current/Channel	5A Max
Working temperature	-20°C~45°C
N.W	62G
Size	125X37X24MM

Product model	GL-C-001P
Input voltage	DC 12-54V
Material	Fireproof material
IP Rate	IP20
G.W	79.4G



Wiring diagram >>>






5-IN-1 ZIGBEE MINI ULTRA THIN CONTROLLER


- Five modes
- Frequency settings
- Power on status Settings
- Remote control
- APP control
- Voice Control



Product name	5in1 Zigbee mini ultra-thin LED controller		
Input voltage	DC 5-24V	Product model	GL-C-002P
Output current	3A Max	Total output current	6A Max
Size	70x36x10MM	IP Rate	IP20
N.W	23.5G	G.W	36.1G
Working temperature	-20°C~45°C		

Product list >>>





1. External push switch

short press it to switch on or switch off the device; long press to adjust the brightness. Note: Push switch only works when device pairing with RF or Zigbee network.






2. Reset

short press once to switch the function; long press for more than 2s to restore factory setting; Note: switch function will clear both zigbee network and RF network.

3. OPT

short press the button to switch on or switch off the device; long press for more than 2s to adjust the brightness.


Wiring diagram >>>



Product name	2 Wires CCT/DIM 2in1 LED Controller Pro		
Input voltage	DC 12-24V	Product model	GL-C-003P
Output current	6A Max	Total output current	10A Max
Size	125x37x24MM	IP Rate	IP20
N.W	62G	G.W	79.4G
Working temperature	-20°C~45°C		






Function Introduction >>>



- ON/OFF RESET**: Short press on/off, long press for more than 5 seconds to reset.
- DIM+ CCT+**: Short press to increase brightness, long press to increase color temperature.
- DIM- CCT-**: Short press to decrease brightness, long press to decrease color temperature.

Product list >>>



Qty: 30pcs/carton
carton size: 465x350x330mm


Product name	Three-button controller set		
Leds/meter	90leds/meter	Power/m	18w/m
Waterproof grade	IP20/IP65	Product model	GL-C-004P
Output current	6A Max	Strip length	2m
Beam angle	120°	Warranty	2Years
LED type	5050RGB	lifespan	35000H
Operating temperature	-20°C~45°C		




Zigbee 3.0 Three-button controller

Gledopto smart zigbee product


Load type >>>



Load Symbol	Load Type	Maximum Load
	Dimmable LED lamps	200W@220V 100W@110V
	Dimmable LED drivers	200W@220V 100W@110V
	Incandescent lighting, HV Halogen lamps	400W@220V 200W@110V
	Low voltage halogen lighting with electronic transformers	200W@220V 100W@110V



Qty: 100pcs/carton
carton size: 340x270x225mm



Function Introduction >>>



Function of "LEVEL" key

- ① ON/OFF
Short press the "Level" key to turn on/off the device.
- ② DIMMER
Long press for adjusting the brightness of light.



Function of "RESET" key

- ① MIN Brightness Setting
Long press "Reset" key to set the "MIN brightness".
Once done, the brightness of the light can only be adjust between the "MIN brightness" and 100% brightness.
- ② RESET
Short press for 5times to RESET the device.



Wiring port

Maximum 2.5mm².



Fireproof material

high temperature resistance.

Product name	Zigbee Triac AC Dimmer		
Model NO.	GL-SD-001	Size	48x45x21mm
Input voltage	100~240V	Output voltage	100~240V
Output current	1.5A Max	IP Rate	IP20
Radio frequency	2.4GHz	Operating temperature	-20°C~60°C

ZIGBEE + RF Digital RGB Strip Controller

Color Horse Racing, Color Bang, Color DJ and others dynamic effects

● ● ●

Color chase

Color flame

Color fade-in/out

Color flowing

Color flicker

Color rainbow

High compatibility >>>



SM16703P



WS2811/WS2812





Flexible lamp strip




G50 bulb string


Wiring diagram >>>




Terminal 1




Terminal 2




Terminal 3




Terminal 4



Terminal 5



Terminal 6






Qty: 100pcs/carton
carton size: 300x270x200mm




Product name	Zigbee + RF Digital RGB Strip Controller		
Model NO.	GL-C-103P	Pixels	300 Max
Input voltage	DC 5~24V	Total output current	10A Max
Size	23.5x48x89mm	IP Rate	IP20
Wire preparation	Φ0.33~2.08mm ²	Operating temperature	-20°C~45°C

RGB+White light Mix >>>



Qty: 100pcs/carton
carton size: 300x270x200mm



Product name	Zigbee 3.0 RGB+CCT LED Controller Pro(MIX)		
Input voltage	DC 12-24-36-48-54V		
Model NO.	GL-C-008P(MIX)	IP Rate	IP20
Output current	5A Max	Total output current	10A Max
N.W.:	54.8g	G.W.:	67.2g
Operating temperature	-20°C~60°C		

ZIGBEE 3.0 PRO

RGB+CCT LED Controller(MIX)

WORKS WITH amazon alexa WORKS WITH Smart life

ZIGBEE

6W/9W/12W LED Downlight Pro

16 Million Colors Changing



Color Temp 2000K~6500K

Brightness Adjustment

Voice Control


Smart Phone APP Control

Wide compatibility



Steps for usage >>>

1. Please open the hole on the ceiling according to the correct size of Diagram 1.
2. Push in the two spring elements, make sure that they are deployed and anchored on the back of the ceiling Diagram 2 and 3.
3. Connect the driver properly according to the wire connection Diagram 4.




Power	6W	9W	12W
Hole Size	100~110mm (3.9~4.3in)	100~110mm (3.9~4.3in)	140~150mm (5.5~5.9in)
Luminous Flux	470~570LM	600~750LM	1000~1200LM
Light efficiency	95LM/W	85LM/W	100LM/W
CRI	>80		
PF	>0.5		
Lifespan	50000 hours		
Input voltage	AC 100~240V		
Color temperature	2200~6500K		
Material	Aluminum+PC cover		




Zigbee 3.0 LED Downlight Pro

6W/12W New style Downlight

- 
IP54
- 
Anti-glare
- 
Brightness controllable
- 
Voice control
- 
16 million colors changing
- 
Smart phone APP control
- 
CCT Adjustable
- 
Controlled by remote control



Qty: 100pcs/carton
carton size: 580x300x230mm



Qty: 36pcs/carton
carton size: 580x300x230mm


	6W	9W
Power	6W	9W
Model NO.:	GL-D-006P	GL-D-007P
Hole size	80mm(3.15in)	95mm(3.74in)
Size	93x93x65mm	113x113x68mm
Luminous flux	280~350LM	660~800LM
G.W	0.3KG	0.38KG
N.W	0.24KG	0.32KG
Light efficiency	60LM/W	67LM/W
CRI	>80	
PF	>0.5	
Lifespan	50000 hours	
Input voltage	AC 100~240V	
Color temperature	2200~6500K	
Material	Aluminum+PC cover	
IP Rate	IP54	

ZigBee 3.0 RGB + WW + CW



6W Downlight Pro

CRI>90
Anti-glare
No flicker

Color temperature adjustable
Brightness adjustable
Color adjustable




Steps for usage >>>



Qty: 50pcs/carton
carton size: 540x370x250mm


Product name	6W LED Downlight	Product model	GL-D-002P
CRI	>90	Input voltage	AC 100~240V
Hole siez	60mm(2.36in)	IP Rate	IP40
SDCM	<5	PF	>0.5
Light efficiency	52LM/W	Luminous flux	270~370LM
Beam angle	60°	Material	Aluminum+PC Cover



Product details >>>



Product list >>>



Qty: 36pcs/carton
carton size: 430x286x415mm

Product Name	6W LED Downlight	Product model	GL-D-001P
CRI	>80	Input voltage	AC100~240V
Light efficiency	75mm(2.95in)	Luminous flux	350~450LM
Hole size	60°	IP Rate	IP40
N.W	238.1G	G.W	295.6G
Beam angle	60°	Installation method	recessed

9W E26 ZigBee 3.0 LED Downlight Pro

The color, color temperature and brightness can be adjustable



16 Million colors changing



Color temperature adjustable




Brightness adjustable




Qty: 20pcs/carton
carton size: 425x405x420mm


Steps for usage >>>




Step 1: Insure power is off, Remove bulb and trim ring. Screw base adapter in to socket.



Step 2: Connect downlight to adapter using the orange connector.



Step 3: Squeeze torsion springs together and release inside of C clips for both sides.



Step 4: Push up the downlight until the trim is flush with ceiling. Ensure no wires are exposed.

Product name	9W E26 Zigbee 3.0 LED Downlight Pro		
Input voltage	AC 100~240V	Product model	GL-D-008P
CRI	>80	Hole size	153mm(6in)
SDCM	<5	IP Rate	IP40
Light efficiency	76LM/W	Luminous flux	580~700LM
Beam angle	120°	Material	Aluminum+PC Cover

2200~6500K

ZIGBEE 3.0 7W LED FILAMENT BULB PRO

Voice control

Remote control

Zigbee connection

APP control

Product details >>>

7W
800LM

A
↑
G

F

64mm (width), 142mm (height)

(GL-B-002P)

60mm (width), 105mm (height)

(GL-B-003P)

95mm (width), 142mm (height)

(GL-B-004P)

Qty: 50pcs/carton
carton size: 380x380x345mm

Qty: 50pcs/carton
carton size: 355x355x275mm


Qty: 50pcs/carton
carton size: 535x535x335mm

LAMP SHADE
The high-quality lampshade has two colors in transparent and brown.

LAMP BEADS
Low heating and high brightness, adjustable brightness and long working life.

E27 LAMP HOLDER
Using E27 lamp holder, suitable for a majority of countries, easy to install, very simple.

Shape	ST64	A60	G95
Model	GL-B-002P	GL-B-003P	GL-B-004P
Size	100~110mm	100~110mm	140~150mm
N.W.	45.3g	31.6g	57.5g
G.W.	87.7g	63.8g	120.8g
Input voltage	220~240V		
Input current	60mA Max 50Hz		
CRI	>80		
Zigbee distance	30m		
RF distance	20m		
Material	Aluminum+Glass		



Product name	Zigbee 4W Candle Bulb Pro		
Input voltage	AC100~240V	Model NO.:	GL-B-001P
CRI	>80	Color temp	2200~6500K
Beam angle	120°	Working Temp	-20°C~45°C
N.W	46.35G	G.W	62.71G
Housing	Plastic+Aluminum		


Product details >>>



Adopt high - grade PMMA Lens, transmittance 93%,The light distribution is more uniform, no dark spots, effectively reduce the adverse glare damage to the eyes.



Fireproof material,high temperature resistance, durable and reliable.



High-quality LED chips, Low fever, high brightness, durable, use life of 50 thousand hours or so.




E12/E14 wide voltage design (100-240V), wide application, durable, universal.



6W
500~550LM

A
G

F




Qty: 50pcs/carton
carton size: 325x325x222mm



12W
900~1100LM

A
G

F



Qty: 50pcs/carton
carton size: 395x395x320mm

Product name	Zigbee 6W LED Bulb Pro		
Input voltage	AC100~240V	Model NO.:	GL-B-007P
CRI	>80	Color temp	2200~6500K
Beam angle	180°	Working Temp	-20°C~45°C
N.W	68.1G	G.W	92.37G
Housing	Plastic+Aluminum		

Product name	Zigbee 12W LED Bulb Pro		
Input voltage	AC100~240V	Model NO.:	GL-B-008P
CRI	>80	Color temp	2200~6500K
Beam angle	220°	Working Temp	-20°C~45°C
N.W	180.52G	G.W	226.92G
Housing	Plastic+Aluminum		

Product details >>>

Adopt imported high - grade PC transparent cover, transmittance 85%, The light distribution is more uniform, no dark spots, effectively reduce the adverse glare damage to the eyes.

The plastic-clad aluminum case is good for heat dissipation, high thermal conductivity, fast heat dissipation, and more durable.

International E27, E26 standard screw base, wide voltage design (100-240V), wide application, durable, universal and saturation can be adjusted.

The Taiwan SMD 3030 LEDs, EPISTAR, Low fever, high brightness, durable, use life of 50 thousand hours or so.

Product details >>>

Adopt imported high - grade PC transparent cover, transmittance 85%, The light distribution is more uniform, no dark spots, effectively reduce the adverse glare damage to the eyes.

The aluminum case is good for heat dissipation, high thermal conductivity, fast heat dissipation, and more durable.

International E27, E26 standard screw base, wide voltage design (100-240V), wide application, durable, universal and saturation can be adjusted.

The Taiwan SMD 3030 LEDs, EPISTAR, Low fever, high brightness, durable, use life of 50 thousand hours or so.

Zigbee LED Spotlight Pro



16 Million colors changing



Brightness dimmable



Color temp adjustable



Smart phone APP control




Voice control



Controlled by remote control




Beam angle: 30°
Low angle, brighter




Beam angle: 120°
High angle, wider

4W
250~300LM



Qty: 100pcs/carton
carton size: 298x298x275mm

Product details >>>



High-quality LED chips, Low fever, high brightness, durable, use life of 50 thousand hours or so.



MR16 Low voltage design(AC/DC 12-24V), more secure, durable, universal.



Adopt high - grade PMMA Lens, transmittance 93%,The light distribution is more uniform, no dark spots, effectively reduce the adverse glare damage to the eyes.



plastic-clad aluminum housing with better heat sink effect, the overall use of no welding process, ensure the quality of products is high, more excellent performance.

Product name		Zigbee 4W MR16 Pro	
Input voltage	AC/DC 12~24V	Model NO.:	GL-S-004P
CRI	>80	Color temp	2200~6500K
Beam angle	30°/120°	Working Temp	-20°C~45°C
N.W	60.0G	G.W	76.5G
Housing	Plastic+Aluminum		

ZIGBEE 3.0

Pro 5W GU10

16 million colors changing


Color temp adjustment

Brightness adjustment


Voice control

Smart phone APP control

Remote Control



5W
300~450LM



Qty: 100pcs/carton
carton size: 298x298x275mm

Product details >>>



High-quality LED chips, Low fever, high brightness, durable, use life of 50 thousand hours or so.



Adopt high - grade PMMA Lens, transmittance 93%,The light distribution is more uniform,no dark spots, effectively reduce the adverse glare damage to the eyes.



GU10 wide voltage design (100-240V), wide application, durable, universal.



The plastic-clad aluminum design has better heat dissipation effect, and the whole adopts no welding process to ensure high product quality and better performance.

Product name	Zigbee 5W RGB CCT GU10 Pro		
Input voltage	AC 100~240V	Model NO.:	GL-S-006P
CRI	>80	Color temp	2200~6500K
Beam angle	30°	Working Temp	-20°C~45°C
N.W	59.2G	G.W	76.3G
Housing	Plastic+Aluminum		

ZIGBEE LED Floodlight Pro

Voice control

Brightness Controllable

16 million colors changing

Smart phone APP control

CCT Adjustable

Controlled by remote control

Product details >>>



Pure aluminium reflector
The reflector is made of pure aluminium (99.8%) which anti-oxidation and unfading in colour,ensuring the reflection.



Tempered glass panel
4 mm tempered glass panel safely protect the lighting source,and the transparent rate is up to 93%.



Wide angel for adjustment
With multiple adjustment points the adjustment angel can be up to 270°.




Stainless steel parts
Endurancing the corrosion of air, chemiccal acid,alkaline,salt and other materials,can be used in all kinds of harsh conditions for long term.



Electrophoretic paint shell
Processed by electrophoretic paint, measured by 200hours salt test,the entire housing has excellent corrosion resistance.

Picture							
Power	10W	10W	30W	60W	100W	200W	400W
Model NO.	GL-FL-001P	GL-FL-004P	GL-FL-005P	GL-FL-006P	GL-FL-007P	GL-FL-008P	GL-FL-010P
Luminous Flux	650~750LM	650~850LM	2100~2700LM	4500~5000LM	7500~8000LM	20000~25000LM	25000~30000LM
Size(mm)	166x107x32	166x107x32	226.5x167x40	309.5x267.5x182.2	402x295x60	470x360x60	480x480x600
NW(g)	473	450	950	1800	3600	8000	14500
GW(g)	573	550	1160	2100	4000	8500	15000
Driver	Customized	Customized	Customized	Mean Well	Mean Well	Mean Well	Mean Well
Input voltage	AC/DC 12V	AC100~240V					
IP Rate	IP65						
Warranty	3years						
LED color	Dual White And Color						
Color temperature	2200K~6500K						
Working temp	-20~60°C						
Line length	0.6m						
Life span	50,000h						
Material	Aluminum, toughened glass						
	Compatible with Zigbee bridge						



12W GARDEN LAMP PRO

- 16 Million colors changing
- Brightness dimmable
- IP65
- Smart phone APP control
- Voice control
- Controlled by remote control

IOS / Android | WORKS WITH amazon alexa

Product details >>>



The Taiwan EPISTAR 3030 chip distribution 15, Low fever, high brightness, durable, use life of 50 thousand hours or so.





It's easy for customers to change the angle.



High quality Aluminum, longer and stronger anticorrosion.




US/UK/AU/EU standard plug, rubber cable x 3M.



Qty: 12pcs/carton
carton size: 490x325x235mm

Product name	Zigbee 12W Garden lamp Pro
Power	12W
Model NO.:	GL-G-101P
Input Voltage	AC 100~240V
Size	120x61x300mm
Luminous Flux	1000~1200LM
G.W	1176.5G
N.W	1030.6G
Beam Angle	25°
CRI	>80
PF	>0.5
Illumination distance	>10m
Color temperature	2200~6500K



ZIGBEE 3.0 7W Garden Light Pro

Gledopto smart zigbee outdoor product



IP66



APP Control




RGB+Dual White



Voice Control

Product details >>>



High lumen led chips

Low power consumption and luminance decrease; Bright color and high brightness.



Power supply

Stable and durable, Protecting the lamp, Lifespan is longer.



Optical lens

Anti-dazzling optical lens; diverging light scientifically. Symmetrical and bright light ray.



High efficiency heat dissipation

Integrative Aluminum design; Inserted thermal conduction, Protect light source lifespan.



Anticorrosion inserted pole

Barb design, longer and bigger.



Power cable nut

Copper nickel plating material, Waterproof and dustproof never rusting.



standard plug

US/UK/AU/EU standard plug. (GL-G-003P does not come with a plug)



Waterproof connector

Waterproof rate: IP68. (Not included in the package)

7W
500~550LM



GL-G-002P




GL-G-003P

Product name	ZigBee 3.0 7W Garden Light Pro	
Input voltage	AC100~240V	AC/DC 24V
Model NO.:	GL-D-002P	GL-D-003P
G.W	597.2G	384.4G
N.W	509.8G	302.4G
Size	Φ75x261mm	
Irradiation distance	10m	
Beam angle	25°	
Material	Aluminum+Toughened glass	

ZIGBEE 3.0 RGB CCT 7W GARDEN LIGHT PRO

■ Wall light (with screws) ■ Garden spike lamp (with a spike)



7W
500~650LM



Product details >>>



High quality Light source
Low power consumption
Bright color and high brightness.



Plastic covered aluminum shell
corrosion-resistant with
good heat dissipation.



Anticorrosion inserted pole
Longer and more stable.



Optical lens
Anti-fire high light transmittance
transparent PC lens.

Product name	ZigBee 3.0 7W Garden Light Pro	
Input voltage	AC100~240V	AC/DC 24V
Model NO.:	GL-D-004P	GL-D-005P
G.W		
N.W		
Size	Φ65x275mm	
Irradiation distance	10m	
Beam angle	25°	
Material	Plastic coated aluminum material Anti-fire transparent PC material	




WiFi SERIES

No gateway required
convenient and fast




Steps for usage >>>



Please connect the light strip, controller, and plug in the power.



Add Device>Lighting>Lighting(Wi-Fi) on Smart Life app to connect your smart controller




Enjoy it!



No hub Required



2.4G WiFi only



Qty: 100pcs/carton
carton size: 340x270x225mm


Input voltage	DC 12~54V	Model NO.:	GL-C-001W
Output Current	5A Max	Total output current	10A Max
IP Rate	IP20	Working Temp	-20°C~45°C
N.W	62G	G.W	79.4G
Size	125x37x24mm	Material	Fireproof material

WiFi LED Controller

- Brightness dimmable
- APP control
- Voice control
- Group control
- Press design



WW/CW controller (GL-C-006W)





RGBW controller (GL-C-007W)



RGB+CCT controller (GL-C-008W)



LED Dimmer controller (GL-C-009W)



Qty: 100pcs/carton
carton size: 300x270x200mm

Product details >>>

Fireproof material
high temperature resistance.

Press type Design
Wiring is more convenient.

Dual White and Color
color, brightness, color temperature and saturation can be adjusted.

WiFi Modules
Wide coverage area and fast transmission speed.

Input voltage	DC12~24~36~48~54V	Model NO.:	GL-C-001W
Output Current	5A Max	Total output current	10A Max
IP Rate	IP20	Working Temp	-20°C~60°C
N.W	57.5G	G.W	69.8G
Size	23.5x48x89mm	Material	Fireproof material
Common anode			
Constant voltage			



OTHER PRODUCTS




Follow your heart's desires
choose the color you like

GLEDOPTO AMBIENT TV BACKLIGHT KIT 2.0

- 
6 Million colors
- 
Hdmi input
- 
Multiple modes
- 
Plug and play
- 
App control
- 
Fashionable durable




Installation diagram >>>



Qty: 20pcs/carton
carton size: 432x368x448mm


Product list >>>




Input voltage	DC 12V	Model NO.:	GL-SN-002K
HDMI	2.0	Strip light length	2M
Sync box size	160x90x20MM	Working Temp	-20°C~60°C
Sync box IP rate	IP20	Light strip IP rate	IP65
N.W	240G	G.W	800G

2.4G RF RGB+CCT Control

Remote control & Wall switch



2.4G RF RGB+CCT Remote control (GL-RC-006Z)



2.4G RF RGB+CCT Wall switch (GL-W-003Z)



Size	18x55x130mm
Material	PC
Transmitting power	6dB
Modulation method	GFSK
Programs	9 kinds
Power	3V(AAA battery*2pcs)
Standby power	15μA
Working temp	-20°C~60°C
Max control range	100 feet(30m)
RF frequency	2.4GHz
Warranty	2 Years

Size	80x80x19mm
Control distance	30m
Transmitting power	6dBm
Modulation method	GFSK
Programs	9 kinds
Input voltage	3V(AAA battery*2pcs)
Standby power	15μA
Radio frequency	2400-2483.5MHz

2.4G RF RGB+CCT REMOTE CONTROL

Color Changeable

CCT Adjustable

Brightness Controllable

8-Zone Control

8 Group management >>>



Usage scenarios

- Living room
- Bedroom
- Kitchen
- Dining room
- Study
- Corridor
- Porch
- Toilet



Size	157x53x18mm
Material	PC
Transmitting power	6dBm
Modulation method	GFSK
Programs	9 kinds
Power	3V(AAA battery*2pcs)
Standby power	15μA
Working temp	-20°C~60°C
Control distance	30m
RF frequency	2.4GHz
Warranty	2 Years



FUNCTION INTRODUCTION

Multifunctional and multi-application.



— smart lighting · happy life —

Function introduction



- **Professional waterproof**

Professional waterproof technology, superior waterproof performance, protection level of IP65, no need to worry about rain and humidity.



- **Smart phone APP control**

You can control the lights in all rooms through the phone app, making your life more convenient.




- **Works with Amazon echo plus**

Adjust on/off , brightness , and change light colors through your voice command.



- **2.4G RF Remote Control**

You can use the remote control to control the light directly, without the zigbee gateway.



- **16Million color changing**

16 Million colors for you to choose and make your life colorful.



- **Color temperature regulation**

Color temperature change from 2200K to 6500K.



- **Brightness adjustment**

Choose the right brightness according to your needs.